

DRYDENE COMPRESSALL® RC 68 ZF

COMPRESSOR OIL



PRODUCT DESCRIPTION

DRYDENE COMPRESSALL® RC 68 ZF is a highly refined, multi-use, zinc-free fluid engineered for many industrial applications. The unique additive chemistry in the RC 68 ZF yields a high-performance ashless anti-wear hydraulic fluid/compressor oil.

PRODUCT APPLICATION

DRYDENE COMPRESSALL® RC 68 ZF compressor oil is designed to provide top perform where OEM specifications are critical to operations. It is an ideal product for use where frequent change outs occur due to poor operating conditions where contamination from acids, solvents, gases, dust or other contaminants may exist.

- Rotary screw compressors
- Reciprocating compressors
- Rotary vane compressors
- Centrifugal compressors
- High pressure turbines
- High pressure hydraulic systems
- Vacuum pumps

FEATURES AND BENEFITS

DRYDENE COMPRESSALL® RC 68 ZF has a useful service life of 2,000 - 3,000 hours under good operating conditions in rotary screw compressors and up to 2,000 hours in reciprocating compressors. In both applications, RC 68 ZF provides the following performance benefits:

- Excellent demulsibility
- Superior rust and oxidation inhibition
- Non-foaming operation
- Environmentally friendly (zinc free)



SPECIFICATIONS

DRYDENE COMPRESSALL® RC 68 ZF compressor oil is suitable for use as anti-wear hydraulic fluid according to:

- Cincinnati Machine P-68, P-69, P-70
- Denison HF-0, HF-1, HF-2
- DIN 51524, Part 2 & 3 (HLP, HVLP)
- ISO 6743/4 (HM, HV)
- AFNOR NF E 48-603 (HM, HV)
- SS 155434
- SEB 181 222
- U.S. Steel 126, 127 & 136

And as compressor oil according to:

- DIN 51506 (VBL, VCL, VDL)
- ISO / DP 6521 (DAA, DAB, DAH, DAG)

DRYDENE COMPRESSALL® RC 68 ZF

COMPRESSOR OIL



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	RC 68 ZF
ISO Grade	ASTM D2422	68
Viscosity @ 40°C, cSt	ASTM D445	68
Viscosity @ 100°C, cSt	ASTM D445	9.2
Viscosity Index	ASTM D2270	112
Pour Point, °C/°F	ASTM D97	-33/-27
Flash Point, °C/°F	ASTM D92	217/424
Copper Corrosion	ASTM D130	1b
Rust - Sea Water	ASTM D665B	Pass
Specific Gravity	ASTM D4052	0.87

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact DRYDENE Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. DRYDENE Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.

841 Nina Way, Unit 1
Warminster, PA 18974
1-877-DRYDENE
www.drydene.com

rev Feb 2019

