

**DRYDENE GEARALL® HEAVY-DUTY GL-5**

HEAVY-DUTY GEAR OIL

**PRODUCT DESCRIPTION**

**DRYDENE GEARALL® HEAVY-DUTY GL-5 GEAR OILS** are high-quality multipurpose, extreme pressure gear oils designed for use in front and rear drive differential systems specifying conventional gear fluids for both service fill and top off.

**PRODUCT APPLICATION**

**DRYDENE GEARALL® HEAVY-DUTY GL-5 GEAR OILS** are designed for use in a wide range of applications where conventional GL-5 fluids are recommended:



- On-highway passenger vehicles, heavy-duty trucks and buses, agricultural and farming equipment
- Recommended for hypoid and bevel gears found in many rear and front differentials
- Suitable for use in manual transmissions where GL-5 fluids are specified
- May be used for service fills, top-off and refills in hypoid and other drive axles specifying API GL-5 gear oils

*\*Can be used for as a top-off fluid in limited slip systems but not intended for filling or refilling applications.*

**FEATURES AND BENEFITS**

**DRYDENE GEARALL® HEAVY-DUTY GL-5 GEAR OILS** are blended to a unique formulation optimized to provide excellent service in all key performance areas:

- Superior torque and load handling capacity
- Helps prevent gear chatter and slippage
- Exceptional protection against thermal and oxidative degradation
- Robust additives help prevent foaming, rust, corrosion and micro-pitting
- Consistent performance in cold and hot operating environments

**SPECIFICATIONS**

- **API GL-5, MT-1**
- **SAE J-2360**
- **MIL-PRF-2105E**
- **Ford WSP-M2C197-A**
- **Meritor Automotive 0-76-D (80W-90), 0-76-A (85W-140)**
- **Navistar B-22, PG-2**
- **Mack GO-J**
- **MAN 342 Type M2 (80W-90), Type M1 (85W-140)**

Other applicable uses may exist. Please contact Drydene Performance Products, Inc. for more information.

rev July 2019



PRODUCT DATA SHEET

# DRYDENE GEARALL® HEAVY-DUTY GL-5

## HEAVY-DUTY GEAR OIL



### TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 80W-90	SAE 85W-140
Viscosity, cSt @ 40°C	ASTM D445	144.2	448.9
Viscosity, cSt @ 100°C	ASTM D445	14.3	29.4
Viscosity Index	ASTM D2270	98	98
Pour Point, °C	ASTM D97	-31	-15
Flash Point, °C	ASTM D92	229	238
Rust Test	ASTM D665	Pass	Pass
Copper Strip Corrosion	ASTM D130	1b	1b
Foam Test	ASTM D892	TR/0	TR/0

All stated physical properties are typical of standard production and may vary.

### DON'T GO THE EXTRA MILE...GO THE EXTRA THOUSAND

Over the past 100 years, we've crushed rocks, built highways, toiled in fields and hauled more cargo than you can imagine. We have no plans of stopping anytime soon, and neither do you.

Drydene stands for integrity, quality and loyalty. Our company has over a century of heritage to back it up. We deliver high-quality lubricants that exceed expectations and set higher industry standards overall, because your lubricants should stand the test of time.

All Drydene heavy-duty and passenger car engine oils, hydraulic fluids, transmission and gear oils, greases as well as our extensive lineup of industrial and specialty fluids are formulated to be as rigorous as the work that needs to be done.

**DRYDENE PERFORMANCE PRODUCTS, INC.**  
841 Nina Way, Unit 1  
Warminster, PA 18974  
[www.drydene.com](http://www.drydene.com)

### HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

### DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

