

DRYDENE RELENTAC® MTS

HEAVY-DUTY WAY LUBRICANT



PRODUCT DESCRIPTION

DRYDENE RELENTAC® MTS fluids are formulated for the lubrication of machine tool slideways, tables and feed apparatus operating under heavy loads where stick slip or table chatter may occur.

PRODUCT APPLICATION

DRYDENE RELENTAC® MTS fluids provide effective lubrication to industrial machine applications where ways are present. They are appropriate for slideways on machining tools as well as milling and screw machines, shapers, planers, lathers and drills.

RELENTAC® MTS fluids are also suitable as light-duty EP lubricants in light to moderately loaded gear boxes stipulating a tackified gear lubricant.



FEATURES AND BENEFITS

DRYDENE RELENTAC® MTS is formulated with premium base oils and specific EP additives to prevent scoring under heavy loading as well as metal wetting agents that help protect against rust and corrosion.

- Advanced additive chemistry promotes molecular bonding to create a protective shield that helps reduce friction and wear
- Resilient tackifiers resist water washout and emulsification with water and coolants used in metalworking
- Prevents stick slip and table chatter which can help extend equipment service life



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	ISO 68	ISO 220
Viscosity @ 40°C, cSt	ASTM D445	68.0	220.0
Viscosity @ 100°C, cSt	ASTM D445	9.0	19.5
Viscosity Index	ASTM D2270	109	102
Pour Point, °C	ASTM D97	-18	5
Flash Point, °F	ASTM D92	425	500
Rust Test	ASTM D4172	Pass	Pass
Timken OK Load, lbs.	ASTM D2782	60	65
Four Ball EP Load Wear Index	ASTM D2596	37.1	46.6
Four Ball Weld Point	ASTM D2596	200	200
Thermal Stability	ASTM D2070	Pass	Pass
Stick Slip	ASTM D2877	.70	.70

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.
 841 Nina Way, Unit 1
 Warminster, PA 18974
www.drydene.com

