

DRYDENE THERMODYNALL® AD-3 DEFOAMER

TRIETHYLENE GLYCOL DEFOAMER



PRODUCT DESCRIPTION

DRYDENE THERMODYNALL® AD-3 DEFOAMER is optimized to provide maximum defoaming and dispersibility in glycol-based fluids used in natural gas dehydration systems.

PRODUCT APPLICATION

DRYDENE THERMODYNALL® AD-3 DEFOAMER can be added directly to dehydration systems without the need for additional blending equipment.

FEATURES AND BENEFITS

Buildup of foam and air entrapment can lead to excess fluid loss and reduce the ability of the fluid to adequately remove water. It controls foam at the first onset as well as long-term to keep dehydration systems functioning at highly efficient rates.



TYPICAL TECHNICAL PROPERTIES

PROPERTY	THERMODYNALL AD-3 DEFOAMER
Color	White
pH of 50% Solution	8.4
Specific Gravity @ 25°C	0.99

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.
 841 Nina Way, Unit 1
 Warminster, PA 18974
www.drydene.com

