

DRYDENE TRANSALL® SYN 50W

SYNTHETIC MANUAL TRANSMISSION FLUID



PRODUCT DESCRIPTION

DRYDENE TRANSALL® SYN 50W is a premium manual transmission fluid formulated from synthetic base oils and the most up-to-date additives to meet the most rigorous demands of modern extended-drain manual transmissions found in both on and off-highway equipment.

PRODUCT APPLICATION

DRYDENE TRANSALL® SYN 50W is recommended for use in a variety of heavy-duty transmission applications:

- Heavy-duty manual transmissions where extended service intervals are required.
- On-highway light and heavy-duty trucks, buses and vans.
- Off-highway segments including construction, mining and agriculture.

SPECIFICATIONS

Eaton Roadranger (E500)

Mack TO-A Plus

ArvinMeritor O-81

Navistar TMS-6816

MIL-PRF-2105E

SAE J2360

API GL-4/MT-1

Eaton PS-164 rev 7

Other applicable uses may exist. Please contact Drydene Performance Products, Inc. for more information.

FEATURES AND BENEFITS

DRYDENE TRANSALL® SYN 50W is designed to maintain exceptional cleanliness all-season performance under even the most extreme conditions.

- Outstanding thermal and oxidative stability help protect critical system parts and extend transmission life.
- Resilient metal-on-metal wear protection even in low-temperature applications.
- Inhibits the formation of sludge and varnish within vital componentry.
- Compatible with most modern engine seal and gasket materials



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	50W
Viscosity @ 40°C, cSt	ASTM D445	139
Viscosity @ 100°C, cSt	ASTM D445	17.4
Viscosity Index	ASTM D2270	145
Pour Point, °F	ASTM D97	-49
Flash Point, °F	ASTM D92	455
Foam Sequences I, II, III	ASTM D892	Pass
Brookfield Viscosity @ -40°C, cP	ASTM D2983	107,400

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact DRYDENE Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. DRYDENE Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.

841 Nina Way, Unit 1
Warminster, PA 18974
www.drydene.com

