

# DRYDENE ALLTEC™ HIGH MILEAGE

SYNTHETIC BLEND / HIGH MILEAGE ENGINE OIL



## PRODUCT DESCRIPTION

**DRYDENE ALLTEC™ HIGH MILEAGE** is formulated for gasoline engines that have exceeded 75,000 miles. The unique additive chemistry helps to condition seals and prevent oil leaks that can occur in higher mileage engines.

## PRODUCT APPLICATION

**DRYDENE ALLTEC HIGH MILEAGE** is intended for use in higher-mileage gasoline engines, both naturally aspirated and turbocharged:

- Passenger cars
- Light-duty trucks
- Sport Utility Vehicles
- New and rebuilt engines




## SPECIFICATIONS

API SP, SN Plus, SN  
 ILSAC GF-6A, GF-5  
 Chrysler MS-6395  
 Chrysler MS-10797  
 Ford WSS-M2C945-B1  
 Ford WSS-M2C960-A1  
 Ford WSS-M2C946-B1  
 GM 6094M

## FEATURES AND BENEFITS

**DRYDENE ALLTEC HIGH MILEAGE** contains a blend of both synthetic and conventional base oils paired with powerful seal conditioners and anti-wear additives to provide extra protection to older engines.

- Robust detergents aid in cleaning built up deposits and sludge in older engines.
- Excellent oxidation stability in all operating conditions.
- Durable oil film strength helps limit metal-on-metal contact in vital combustion chamber and valve train components.
- Helps reduce friction and oil consumption in engines that have exceeded 75,000 miles



## TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 5W-20	SAE 5W-30
Viscosity @ 40°C, cSt	ASTM D445	51.36	63.54
Viscosity @ 100°C, cSt	ASTM D445	8.74	10.80
Viscosity Index	ASTM D2270	150	162
Cold Cranking Simulator @ (°C), cP	ASTM D5293	6305 (-30)	5704 (-30)
Color	ASTM D1500	3.0	3.0
Flash Point °C	ASTM D92	206	204
High Temperature/High Shear Vis @150°C, cP	ASTM D5481	2.74	3.16
Noack Volatility, % loss	ASTM D6375	14.8	14.2
Pour Point °C (°F)	ASTM D5950	-44°C (-47°F)	-44°C (-47°F)
Pumping Viscosity @ (°C), cP	ASTM D4684	23,600 (-35)	28,400 (-35)
Shear Stability, Final Viscosity in cSt	ASTM D6278	7.31	8.50

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit [www.DRYDENE.com](http://www.DRYDENE.com)

