

DRYDENE RELETAC® RDX

PNEUMATIC AIR TOOL/ROCK DRILL OIL



PRODUCT DESCRIPTION

DRYDENE RELETAC® RDX fluids are specially formulated for the rigorous operating conditions common to various types of pneumatic air and high-pressure percussion pneumatic air tools as well as mist lubrication in general purpose air tools.

PRODUCT APPLICATION

DRYDENE RELETAC® RDX fluids are recommended for use in a wide variety of construction and mining equipment including where exposure to moisture and extreme conditions may occur:

- Rock drills
- Jack hammers
- Air drills
- Sinkers

SPECIFICATIONS

Ingersoll-Rand
Gardner-Denver
Chicago Pneumatic
Cincinnati Machine/Milacron

*Other applicable uses may exist. Please contact Drydene Performance Products, Inc. for more information.

FEATURES AND BENEFITS

DRYDENE RELETAC® RDX products contain special additives which both protect heavily-loaded components under extreme pressure even in conditions where moisture may be present.

The additive system also provides protection against various undesirable conditions including metal-on-metal wear, rusting, oxidation and corrosion.



TYPICAL TECHNICAL PROPERTIES

| PROPERTY | TEST METHOD | ISO 100 | ISO 320 |
|------------------------|-------------|---------|---------|
| Viscosity @ 40°C, cSt | ASTM D445 | 100 | 320 |
| Viscosity @ 100°C, cSt | ASTM D445 | 10.7 | 23.9 |
| Viscosity Index | ASTM D2270 | 98 | 96 |
| Flash Point, °F | ASTM D92 | 420 | 450 |
| Timken EP Test, lbs. | ASTM D2782 | 60 | 60 |
| Falex Load Test, lbs. | ASTM D3233 | 2200 | 2200 |
| Steam Emulsion No. | ASTM D1935 | 1200+ | 1200+ |
| Corrosion | ASTM D130 | 1B | 1B |

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.

841 Nina Way, Unit 1
Warminster, PA 18974
1-877-DRYDENE
www.drydene.com

