

DRYDENE RETRAPLEX® TOPAZ GREASE

HEAVY-DUTY MULTI-PURPOSE GREASE



PRODUCT DESCRIPTION

DRYDENE RETRAPLEX® TOPAZ GREASE is a premium heavy-duty multi-purpose grease designed for use in medium to moderate load applications where added protection for extreme pressure and high operating temperatures is needed.

PRODUCT APPLICATION

DRYDENE RETRAPLEX® TOPAZ GREASE can be used in a wide variety of both automotive and heavy equipment applications especially where product consolidation is desired.

- Passenger cars and pickup trucks
- Disc brakes and wheel bearings
- Over-the-road trucks and buses
- Agricultural equipment
- Off-road equipment

Other applicable uses may exist. Please contact Drydene Performance Products, Inc. for more information.

FEATURES AND BENEFITS

DRYDENE RETRAPLEX® TOPAZ GREASE is built with superior extreme pressure and anti-wear additives to ensure consistent performance across a variety of applications and operating conditions.

- Optimal extreme pressure and temperature operations, especially disk brake bearings.
- High dropping point
- Excellent thermal and shear stability
- Protection against wear and corrosion
- Outstanding year-round performance in both low and high temperatures
- Proprietary inhibitors resist oxidation and leakage



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TOPAZ EP 2
NLGI Grade		2
Thickener Type	ASTM D128	Lithium Complex
Color	Visual	Amber
Appearance	Visual	Smooth/Very Tacky
Penetration @ 77°F, 60 Strokes	ASTM D217	265 - 295
Dropping Point, °F	ASTM D2265	525 min
Base Oil Viscosity, cSt @ 40°C	ASTM D445	90 - 110
Timken OK Load, lbs	ASTM D2509	60
Four Ball EP Weld Point, kg	ASTM D2596	400
Four Ball EP Load Wear Index	ASTM D2596	30
Four Ball Wear Scar, mm	ASTM D2266	0.6 max
Water Washout @ 175°F	ASTM D1264	0.5

All stated physical properties are typical of standard production and may vary.

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.
 841 Nina Way, Unit 1
 Warminster, PA 18974
www.drydene.com

