

DRYDENE HIGH MILEAGE PLUS MOTOR OIL

SYNTHETIC BLEND / HIGH MILEAGE ENGINE OIL





PRODUCT DESCRIPTION

DRYDENE HIGH MILEAGE PLUS MOTOR OIL is formulated for gasoline engines that have exceeded 75,000 miles. The unique additive chemistry helps to condition seals to prevent oil leaks that can occur in higher mileage engines.

PRODUCT APPLICATION

DRYDENE HIGH MILEAGE PLUS is intended for use in high-mileage gasoline engines, both naturally aspirated and turbocharged:

- Passenger cars
- Light-duty trucks
- Sport Utility Vehicles
- New and rebuilt engines



FEATURES AND BENEFITS

DRYDENE HIGH MILEAGE PLUS help protect modern engines that have already exceeded 75,000 miles and still demand maximum performance and longevity:

- Contains powerful seal conditioners to help reduce leakage and oil consumption
- Robust detergents aid in cleaning built up harmful deposits and sludge
- Better control of sludge, high temperature deposit formation and viscosity increase than previous generation gasoline engine oils
- Can be used in Turbocharged Gasoline Direct Injection (TGDI) engines that may experience Low-Speed Pre-Ignition (LSPI).
- Durable anti-wear additives protect critical engine parts and surfaces that have worn over time
- Enhanced oxidation safeguards, corrosion prevention and engine cleanliness

SPECIFICATIONS

- API SP, SN Plus, SN
- ILSAC GF-6A, GF-5
- Chrysler MS-6395
- Chrysler MS-10797
- Ford WSS-M2C945-B1
- Ford WSS-M2C930-A
- Ford WSS-M2C153
- Ford WSS-M2C960-A1
- GM 6094M

DRYDENE HIGH MILEAGE PLUS MOTOR OILS are backward compatible for previous API and ILSAC categories for gasoline engine oils.



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 5W-20	SAE 5W-30
Viscosity @ 40°C (cSt)	ASTM D445	51.7	67.5
Viscosity @ 100°C (cSt)	ASTM D445	8.9	11.2
Viscosity Index	ASTM D2270	152	159
Flash Point, °C/°F	ASTM D92	220/428	220/428
Pour Point, °C/°F	ASTM D5950	-45/-49	-45/-49
Cold Cranking Simulator @ °C, cP	ASTM D5293	5140	5480
High Temp/High Shear Vis @ 150°C, cP	ASTM D5481	2.67	3.13
NOACK Volatility, % loss	ASTM D5800	13.0	12.0
High Temperature Foaming, static foam	ASTM D6082 (Opt A)	20/0	20/0
TBN, mg KOH/g	ASTM D2896	7.0	7.0

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.DRYDENE.com

