

DRYDENE AQUALORICA™ ST

WATER SOLUBLE RUST INHIBITOR

**PRODUCT DESCRIPTION**

DRYDENE AQUALORICA™ ST is a water-based amine borate designed for short-term protection of ferrous and non-ferrous metals and machined parts against rust for up to six months when stored indoors. It may be applied as received or in dilutions with water.

PRODUCT APPLICATION


DRYDENE AQUALORICA ST may be applied as a spray or by immersion as received or with water. It is recommended to being with a dilution rate of 10:1 to test delivery and coverage of surfaces to be treated.

It can be easily cleaned from parts and surfaces with water and an alkaline cleaner.

FEATURES AND BENEFITS

DRYDENE AQUALORICA ST does not contain any petroleum or solvent content and will not leave a tacky film behind when dried. Its low-foaming formula is extremely stable, even when used with hard water in dilutions as low as 5%.

AQUALORICA ST is well suited for use a leak test fluid for pressure vessels, tanks and other sealed containers.

**TYPICAL TECHNICAL PROPERTIES**

PROPERTY	TEST METHOD	AQUALORICA™ ST
Color	Visual	Light yellow
Density, lbs/gal	Physical	8.82
Appearance	Visual	Clear liquid
Odor	Physical	Mild
pH, 10:1 solution	ASTM D1172	9.2 -10.0
Specific Gravity	ASTM D891	1.058
Refractometer, 5%	Physical	0.9
Refractometer, 10%	Physical	1.8

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and/or API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.

841 Nina Way, Unit 1
Warminster, PA 18974
www.drydene.com

