

**DRYDENE BIODYNALL™ PLUS**

COOLANT CONDITIONER / BIOCID

**PRODUCT DESCRIPTION**

**DRYDENE BIOSYNALL™ PLUS** is a broad-spectrum amine-based metalworking coolant conditioner designed to inhibit the growth of fungus and bacteria.


**PRODUCT APPLICATION**

**DRYDENE BIODYNALL PLUS** should be used at a rate of 1 U.S. pint (16 oz) per 100 gallons of diluted metalworking fluid.

After adding, the system should be allowed to circulate before resuming normal machining operations.

**FEATURES AND BENEFITS**

**DRYDENE BIODYNALL PLUS** provides outstanding protection against the growth of bacteria and fungus as well as buffering coolant pH within metalworking fluid storage and delivery systems.

**TYPICAL TECHNICAL PROPERTIES**

PROPERTY	TEST METHOD	BIODYNALL™ PLUS
Color	Visual	Colorless
Density, lbs/gal	Physical	7.91
Appearance	Visual	Clear, liquid
Odor	Physical	Mild
pH, 10:1 solution	ASTM D1172	10.0 - 12.0
Specific Gravity	ASTM D891	0.950

**HEALTH AND SAFETY**

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

**DISCLAIMER**

Always follow OEM recommendations for fluid viscosity and/or API service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

**DRYDENE PERFORMANCE PRODUCTS, INC.**

841 Nina Way, Unit 1  
Warminster, PA 18974  
www.drydene.com

