

DRYDENE VERSOLSYN™ PLUS

SYNTHETIC MACHINING COOLANT

**PRODUCT DESCRIPTION**

DRYDENE VERSOLSYN™ PLUS is a medium-duty, boron-free synthetic coolant fortified with premium extreme pressure additives to provide exceptional machining, grinding and boring performance when working cast iron or steel alloys while keeping economical considerations in mind. Its excellent wetting and oil rejecting properties deliver longer tool and sump life which can lower overall operating costs.

PRODUCT APPLICATION

DRYDENE VERSOLSYN PLUS is recommended for light and medium-duty machining processes of cast iron and steel alloys in both single sump and central reservoir systems.

- Surface grinding
- Light and medium drilling and boring
- Milling and turning
- Broaching and sawing
- General machining



Versolsyn Prime is typically diluted with water at 5% - 8% depending on the application metal type.

**FEATURES AND BENEFITS**

DRYDENE VERSOLSYN PLUS is an ideal choice when superior machining performance and economics are key factors when choosing a fluid:

- Highly effective at rejecting tramp oil
- Keeps tool surfaces clean by preventing the buildup of chips
- Low foaming, stable formula in both soft and hard water applications
- Extends sump life without the use of
- Chlorine free additive technology
- Protects against rust and corrosion

VERSOLSYN PLUS is formulated without the use of boron, formaldehydes, chlorine and nitrites which can be advantageous where statutory requirements may prohibit their use or introduction into waste or disposal chains.

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	PLUS
Color	Physical	Amber
Appearance	Physical	Clear
Odor		Characteristic
Specific Gravity @ 60°F	ASTM D891	1.04
Density, lbs/gal	Physical	8.65
pH @ 10%	ASTM D1172	9.0 - 9.9
Refractometer, 10%	Refractometer	4.5
Chlorine		none
Boron		none

HEALTH AND SAFETY

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

DISCLAIMER

Always follow OEM recommendations for fluid viscosity and/or service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

DRYDENE PERFORMANCE PRODUCTS, INC.

841 Nina Way, Unit 1
Warminster, PA 18974
www.drydene.com

