

**DRYDENE AQUALORICA™ LT**

WATER SOLUBLE RUST INHIBITOR

**PRODUCT DESCRIPTION**

**DRYDENE AQUALORICA™ LT** is a water-based corrosion inhibitor designed for short-term protection of ferrous and non-ferrous metals components against rust for up to 1 year indoor storage. The inhibitor formula is borate, petroleum and VOC-free for improved operator safety.

**PRODUCT APPLICATION**

**DRYDENE AQUALORICA LT** should not be used at a concentration rate above 25% by volume.

When Paint will be Applied:	1 - 3%BV
Long-Term Internal Corrosion Protection:	5 - 20%BV
Recommended starting concentration:	5% BV
Operating range:	70-170° w/o foam

**FEATURES AND BENEFITS**

**DRYDENE AQUALORICA LT** does not contain any petroleum content and will not leave a tacky film behind when dried. Its low-foaming formula is extremely stable and does not interfere with paint adhesion or gauging measurements.

**Aqualorica ST** contains powerful corrosion inhibitors that help protect ferrous, brass, bronze and copper metals.

It can be easily cleaned from parts and surfaces with water and an alkaline cleaner.

**TYPICAL TECHNICAL PROPERTIES**

PROPERTY	TEST METHOD	AQUALORICA™ LT
Color	Visual	Amber
Appearance	Visual	Clear liquid
Odor	Physical	Mild
pH, 5% solution	ASTM D1172	9.1
Specific Gravity	ASTM D891	1.03
Phosphate Content		none
Biodegradability		100%

**HEALTH AND SAFETY**

May cause irritation to the eyes upon contact. Avoid eye contact. For industrial and commercial use only.

For a copy of this product's Safety Data Sheet (SDS), contact Drydene Performance Products, Inc. at 1-877-DRYDENE.

**DISCLAIMER**

Always follow OEM recommendations for fluid viscosity and/or service category. Drydene Performance Products, Inc. assumes no responsibility for product misuse or improper application.

**DRYDENE PERFORMANCE PRODUCTS, INC.**

841 Nina Way, Unit 1  
Warminster, PA 18974  
www.drydene.com

