



PRODUCT DATA SHEET

DRYDENE BIODYNALL™ PLUS

COOLANT CONDITIONER / BIOCIDES



PRODUCT DESCRIPTION

DRYDENE BIODYNALL™ PLUS is a broad-spectrum amine-based metalworking coolant conditioner designed to inhibit the growth of fungus and bacteria.

FEATURES AND BENEFITS

DRYDENE BIODYNALL PLUS provides outstanding protection against the growth of bacteria and fungus as well as buffering coolant pH within metalworking fluid storage and delivery systems.

PRODUCT APPLICATION

DRYDENE BIODYNALL PLUS should be used at a rate of 1 U.S. pint (16 oz) per 100 gallons of diluted metalworking fluid.

After adding, the system should be allowed to circulate before resuming normal machining operations.



TYPICAL TECHNICAL PROPERTIES



PROPERTY	TEST METHOD	BIODYNALL™ PLUS
Color	Visual	Colorless
Density, lbs/gal	Physical	7.91
Appearance	Visual	Clear, liquid
Odor	Physical	Mild
pH, 10:1 solution	ASTM D1172	10.0 - 12.0
Specific Gravity	ASTM D891	0.950

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.DRYDENE.com Rev (0422-01)



RelaDyne, LLC. | 8280 Montgomery Road, Suite 1 | Cincinnati, OH 45236 | 1-888-830-3156 | WWW.RELADYNE.COM

