



PRODUCT DATA SHEET

DRYDENE DIESELALL® HD ENGINE OILS

HEAVY-DUTY DIESEL ENGINE OIL



PRODUCT DESCRIPTION

DRYDENE DIESELALL® HD ENGINE OILS are premium low ash engine oils designed for use in older model diesel engines in both on-highway and off-highway applications as well as off-highway hydraulic systems requiring a 10W engine oil.

PRODUCT APPLICATION

DRYDENE DIESELALL HD ENGINE OILS are recommended for use in a variety of older model heavy-duty diesel and gasoline engine applications:

- Heavy equipment used on off-road mining, construction, agriculture and forestry operations
- Mixed fleets with on-highway diesel engines and smaller light-duty diesel and gasoline engines
- May be used in hydraulic and transmission systems where monograde engine oils are specified based on manufacturer guidelines

SPECIFICATIONS

API CF
 API CF-2 (SAE 30, 40, 50)
 API SL
 MIL-L-46152G
 Allison C4, C3
 Caterpillar ECF-1
 Cummins CES 20078, 20077, 20076, 20071
 Detroit Diesel 7SE 270 Series 51, 71, 92
 Ford M2C153G
 GM 6094M
 Mack EO-N, EO-M Plus, EO-M
 Volvo VDS-2, VDS

FEATURES AND BENEFITS

DRYDENE DIESELALL HD ENGINE OILS are blended from premium base stocks and specific additives to provide dual-purpose performance in both crankcase and hydraulic systems.

- Detergent and dispersant additives help maintain engine cleanliness, suppress varnishing and aids in suspension of soot and contaminants in the oil.
- Robust anti-wear additives help extend regular drain intervals and overall engine life even in high operating temperature applications.
- Reliable performance in cold weather applications, especially in hydraulic systems (SAE 10W)



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	SAE 10W	SAE 30W	SAE 40W	SAE 50W
Viscosity @ 100°C, cSt	ASTM D445	6.2	11.2	14.5	18.5
Viscosity @ 40°C, cSt	ASTM D445	37.0	88.0	133.0	192.0
Viscosity Index	ASTM D2270	115	115	108	107
Pour Point, °C/°F	ASTM D97	-33/-27	-21/-6	-18/0	-12/10
Color	ASTM D1500	2.5	2.5	4.5	5.0
TBN, mgKOH/g	ASTM D2896	8.0	8.0	8.0	8.0

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.DRYDENE.com Rev (0322-01)



RelaDyne, LLC. | 8280 Montgomery Road, Suite 1 | Cincinnati, OH 45236 | 1-888-830-3156 | WWW.RELADYNE.COM

