



PRODUCT DESCRIPTION

DRYDENE SOLORICA™ S is a solvent based, barium-free inhibitor for the long-term (up to 12 months indoors) prevention rust and corrosion on both ferrous and non-ferrous surfaces. Solorica S effectively displaces water, machining fluids and cleaner residues with a thin dry, film that is easy to clean after periods of storage.

PRODUCT APPLICATION

DRYDENE SOLORICA S may be applied to corrosion-prone surfaces by a variety of methods:

- Spraying/Flow coating
- Dipping/Immersion where water displacement is desired
- Rolling, Brushing and Swabbing

Solorica S should be used as received and will cover up to 1200 square feet per gallon (depending on temperature, application method and surface porosity).


FEATURES AND BENEFITS

DRYDENE SOLORICA S offers versatility and functionality across a range of key areas:

- Longer storage periods than high flash solvents (up to one year indoors)
- Outstanding protection against salt spray and humidity
- Leaves a thin, dry film after drying to protect treated surfaces which can be removed with basic alkaline cleaners
- Highly polar formula forms resilient bonds to ferrous surfaces which help displace water and moisture
- Non-staining formula is safe for use on cast iron, steels and castings



TYPICAL TECHNICAL PROPERTIES



| PROPERTY | TEST METHOD | SOLORICA™ S |
|-------------------------|-------------|------------------|
| Color | Visual | Clear |
| Appearance | Visual | Colorless liquid |
| Odor | Physical | Mild petroleum |
| Viscosity @ 40°C, cSt | ASTM D445 | <20 |
| Flash Point, TCC °F | ASTM D56 | 145 |
| Specific gravity @ 15°C | ASTM D891 | 0.81 |
| % Volatile, wt. | | 80 |

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.DRYDENE.com Rev (0422-01)