



## PRODUCT DESCRIPTION

**DRYDENE VERSOLCUT™ X2** is a semi-synthetic, medium-duty machining and grinding coolant designed to provide premium performance metal cooling and wetting without the use of chlorinated paraffins or formaldehyde on aluminum, steel and cast iron. The complex additive system is biostable and delivers excellent surface finishing.

## PRODUCT APPLICATION

**DRYDENE VERSOLCUT X2** is fortified with extreme pressure additives that delivers superior metal cooling in a variety of applications:

- Grinding
- CNC milling
- Drilling and tapping
- Turning
- General machining

*Typical use dilution (in water) for machining applications is 5% to 10%*


## FEATURES AND BENEFITS

**DRYDENE VERSOLCUT X2's** semi-synthetic formula offers many advantages to metalworking operators handling a variety of metal types:

- Contains no chlorinated paraffins or nitrites making it an ideal choice where environmental considerations are important in selecting a fluid
- Exceptional wetting of worked surfaces during machining and grinding
- Durable releasability without the use of formaldehydes
- Fortified with corrosion inhibitors to protect machining equipment
- Helps reduce overall operating costs by providing extended fluid and machine tool life



## TYPICAL TECHNICAL PROPERTIES



PROPERTY	TEST METHOD	VERSOLCUT X2
Color	Visual	Gold
Appearance	Visual	Clear
Odor	Physical	Characteristic
Specific Gravity @ 60°F	ASTM D891	0.995
Density, lbs/gal	Physical	8.29
pH @ 10%	ASTM D1172	9.4 - 10.2
Refractometer, 5%	Refractometer	2.6
Refractometer, 10%	Refractometer	5.3
Chlorine	-	none
Formaldehydes	-	none

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit [www.DRYDENE.com](http://www.DRYDENE.com) Rev (0422-01)